

**INCLUSION OF TROPICAL STORMS  
FOR THE COMBINED TOTAL STORM TIDE FREQUENCY RESTUDY  
FOR SARASOTA COUNTY, FLORIDA**

**Sponsored by  
Florida Department of Environmental Protection,  
Bureau of Beaches and Coastal Systems**



**Submitted by  
Beaches and Shores Resource Center  
Institute of Science and Public Affairs  
Florida State University**

**May 2011**

## Table of Contents

1.0	Background .....	1
2.1	Introduction and Data Source .....	1
2.2	Storm Frequency and Direction .....	1
2.3	Radius to Maximum Winds and Central Pressure Deficit .....	2
2.4	Forward Speed .....	5
2.5	Track Position .....	5
3.1	Simulation of a n-Year Sequence of Storm Associated Storm Tides .....	7
3.2	Simulation .....	9
3.3	Computation of Return Periods .....	10
4.0	Results .....	11
	REFERENCES .....	13
	APPENDIX A .....	14
	APPENDIX B .....	17

## List of Figures

<u>Figure</u>		<u>Page</u>
1	Cumulative Probability Distribution of Storm Track Direction, $\theta_N$	2
2	Cumulative Probability Distribution of Radius to Maximum Winds, R, for Landfalling and Exiting Storms	3
3	Cumulative Probability Distribution of Radius to Maximum Winds, R, for Alongshore Storms	3
4	Cumulative Probability Distribution of Central Pressure Deficit, $\Delta p$ for Landfalling and Alongshore Storms	4
5	Cumulative Probability Distribution of Central Pressure Deficit, $\Delta p$ for Exiting Storms	
6	Cumulative Probability Distribution of Storm Translation Speed, $V_F$	5
7	Cumulative Probability Distribution of Landfalling Distance, $Y_F$ , for Landfalling And Exiting Storms	6
8	Cumulative Probability Distribution of Offshore Distance, $X_L$ , for Alongshore Storms	6
9	Flow Chart for Two-Dimensional Storm Tide Simulations	8
10	Combined Total Storm Tide Elevation Versus Return Period for Study Area	11

## List of Tables

<u>Table</u>		<u>Page</u>
I	Combined Total Storm Tide Values for Various Return Periods	12

## **1.0 Background**

In accordance with the objectives and rationale of the Florida Coastal Construction Control Line, the establishment of the line is based on the damage potential of 100 year return period hurricanes. A report entitled "Combined Total Storm Tide Frequency for Sarasota County, Florida" (Reference (1)) was submitted to FDEP in October, 1988. This study is requested by the FDEP to include the most updated tropical storms and hurricanes in the storm surge simulations. Since the methodology and procedures used for this study are the same as for the report mentioned above, only the storm statistics and the results are presented in this report.

### **2.1 Introduction and Data Source**

The statistical parameters are based on historical storm data as presented in References (2) and (3). In brief, the empirical cumulative probability distributions are plotted for each of the parameters of interest and are then approximated by a series of straight line segments for computer application. All of the parameters are considered to be independent. The following subsections describe the statistical characteristics of the individual parameters of interest.

### **2.2 Storm Frequency and Direction**

The storms causing appreciable storm tides in the vicinity of the Sarasota County shoreline are classified as "landfalling", "exiting" or "alongshore" storms. Reasonably good data are available describing the characteristics of the storms impacting the area from 1900 to 2009. For purposes of this report, the data contained in References (2) and (3) that fall within a 300 n. mi. segment of the coast comprising the study area are used. The storm direction is defined here as the azimuth from which the storm is translating at the time of landfall, or, if an alongshore storm, when in close proximity to the site.

For purposes of this study, landfalling and exiting storms are considered to be of possible significance if they made landfall within a 300 n. mi. segment of the coast comprising the study area. This segment is extended 150 n. mi. north and 150 n. mi. south from the midpoint of the Sarasota County shoreline. Accordingly, there were 53 landfalling, 20 exiting and 9 alongshore storms occurring in the years 1900 through 2009. The table in Appendix A lists the storms used in this study.

Based on historical data, it is expected that within a 1,000 year period a total of 745 storms will occur within the 300 n. mi. segment of the coast comprising the study area. Of the 745 storms, 481 will be landfalling, 182 exiting and 82 alongshore storms.

For purposes of computer use, the cumulative probability distribution of storm track direction ( $\theta_N$ ) is presented in Figure 1.




Figure 1 Cumulative Probability Distribution of Storm Track Direction,  $\theta_N$

### 2.3 Radius to Maximum Winds and Central Pressure Deficit

The cumulative probability distribution of radius to maximum winds for landfalling and exiting storms is presented in Figures 2. Figure 3 presents the same for alongshore storms. The cumulative probability distributions of pressure deficit for landfalling and alongshore storms is presented in Figure 4. Figure 5 presents the same for exiting storms.




Figure 2 Cumulative Probability Distribution of Radius to the Maximum Wind, R, for Landfalling and Exiting Storms




Figure 3 Cumulative Probability Distribution of Radius to the Maximum Wind, R, for Alongshore Storms




Figure 4 Cumulative Probability Distribution of Central Pressure Deficit,  $\Delta p$  for Landfalling and Alongshore storms




Figure 5 Cumulative Probability Distribution of Central Pressure Deficit,  $\Delta p$  for Exiting storms



## 2.4 Forward Speed

The cumulative probability distribution of the forward speed of translation for landfalling, exiting and alongshore storms is presented in Figure 6.




Figure 6 Cumulative Probability Distribution of Translation Speed ,  $V_F$

## 2.5 Track Position

For the landfalling and exiting storms, the track position is determined by the y coordinate,  $Y_F$ , representing the landfalling or exiting point. Figure 7 presents the cumulative probability distribution for the actual landfalling and exiting position,  $Y_F$ , for landfalling and exiting storms. Figure 8 presents the cumulative probability distribution for the actual offshore distance,  $X_L$ , for alongshore storms.




Figure 7 Cumulative Probability Distribution of Landfalling Distance,  $Y_F$ , for Landfalling and Exiting Storms




Figure 8 Cumulative Probability Distribution of Offshore Distance,  $X_L$ , for Alongshore Storms

### 3.1 Simulation of a n-Year Sequence of Storm Associated Storm Tides

With the statistical characteristics of historical storms available and the two-dimensional model calibrated as described in the preceding section, the simulation shown in Figure 9 is carried out.

The first phase of the simulation comprises the selection of the storm characteristics in accordance with the historical data. In each storm, this involves the following:

- 1) Quantifying  $\Delta p$ ,  $R$ ,  $V_F$ ,  $\theta_N$  and storm track in accordance with the historical probabilities.
- 2) For these characteristics, a random astronomical tide from the storm season is generated as a boundary condition to the two-dimensional numerical model and the model is run to determine the storm surge at the site of interest. This storm surge with dynamic wave set up is then adjusted in accordance with the factors obtained from the two-dimensional model calibration runs for the landward grid at each time step to yield the combined total storm tide.
- 3) Determining whether enough storms have been simulated for the n-year simulation.
- 4) After the required number of storms and associated storm tides have been simulated, the peak water levels for each storm are ranked and the return period,  $TR$ , is calculated, according to

$$TR = 1000/M$$

where  $M$  is the rank of the combined total storm tide level. (For example, since the simulation was carried out for a 1,000 year period, the highest combined total tide level would have a return period of 1,000 years, the tenth highest water level would have a return period of 100 years, etc.). Finally, by presenting these results on semi-log paper, it is possible to interpolate return periods of 5, 10, 15, 20, 25, 30 and 50 years.




Figure 9 Flow Chart for Two-Dimensional Storm Tide Simulations

### 3.2 Simulation

To summarize information presented earlier, this phase includes the simulation of the occurrence of 1,000 years of storms along a shoreline segment of 300 n. mi. The simulated storms are given directional distributions according to Figure 5. In an average 1,000 year period, there would be a total of 745 storms.

Selection of Storm Parameters - Each of the five idealized storm parameters, [Radius to Maximum Winds,  $R$ ; Central Pressure,  $p_o$  (or Central Pressure Deficit,  $\Delta p$ ); Track Direction,  $\theta_N$ ; System Forward Speed,  $V_F$ ; and Track Position] is determined randomly in accordance with the associated cumulative probability distribution functions. The procedure is described below for the track direction,  $\theta_N$ , and is similar for all other variables.

The approximate piece-wise linear cumulative probability distribution function for track direction,  $\theta_N$ , is shown in Figure 5. The nature of this function is such that the predominant directions are those where the function rises steeply. To randomly select a track direction in accordance with the distribution function, the computer first generates a random number between 0 and 1 and then selects the  $\theta_N$  corresponding to that cumulative probability. The other four parameters are determined similarly with a separate and independent random number being generated for each parameter and the appropriate cumulative probability distribution used.

Calculation of Storm Surge with the Effect of Astronomical Tide - A particular storm can be "phased" such that the maximum resulting storm surge is increased or decreased by astronomical tidal fluctuations. Considering the predicted ocean astronomical tidal fluctuations at Captiva Island from June 1 to November 30, 1984 to be representative of those occurring during the storm season and assuming the phasing of storm occurrence and astronomical tides to be independent, the combination of these tidal components is carried out in the following manner.

With the storm parameters established, a starting time for the storm is selected randomly between June 1 and November 30, 1984. The corresponding astronomical tide at the starting time is generated and varies with time thereafter according to the input astronomical tide data. The calculation of the storm surge history by the calibrated two-dimensional model is thus phased with the astronomical tide to yield the combined storm surge and astronomical tide water level history at the site of interest.

### 3.3 Computation of Return Periods

With a sufficient number (745) of maximum combined total storm tides simulated to represent a typical 1,000 year time interval, the tides associated with various return periods of interest are determined. The 745 maximum combined total storm tides are ranked in descending order with the largest occurring first. The return period, TR, of the ranked tides is then

$$TR = 1000 / M$$

in which

TR = Return period in years between expected exceedances of the associated maximum storm tide

M = Rank of maximum storm tide

As an example, for M = 745 (associated with the lowest water level) the return period would be:

$$TR_{745} = 1000 / 745 = 1.34 \text{ years}$$

which indicates that the smallest storm tide could be expected to be exceeded approximately once every 2 years. As a second example, the return period for M = 20 is

$$TR_{20} = 1000/20 = 50 \text{ years}$$

The ranked maximum combined total storm tides and associated return periods can be plotted and the combined total storm tide associated with any return period determined. Finally, it is noted that it is possible to run the simulation procedure any number of times to determine the stability (constancy) of any combined total storm tide associated with a given return period. It is expected that for a 1,000 year simulation, the storm tides associated with the longer (> 250 year) return periods would not be well-defined by one simulation and would exhibit variation from simulation to simulation. However, the storm tides associated with the lower return periods (TR < 100 years) should be well-defined by a 1,000 year simulation and hence are not expected to vary significantly for various simulations.

## 4.0 Results

Five 1,000-year simulations for Sarasota County were carried out employing the computer methods and storm statistics presented in the preceding sections. The combined total storm tides above NGVD and the associated return periods are plotted on semi-log paper in Figure 10. Each data point represents the average value of five simulations and a curve drawn through the data points is adopted to represent the tide-frequency relationship.




Figure 10 Combined Total Storm Tide Elevation Versus Return Period for Study Area

Table I below gives the combined total storm tide values and corresponding return periods for Sarasota County.

Table I

Combined Total Storm Tide Levels (ft.) for Various Return Periods

Return Period, TR (years)	North Profile NGVD29	North Profile NAVD88	Middle Profile NGVD29	Middle Profile NAVD88	South Profile NGVD29	South Profile NAVD88
50	10.5	9.5	10.6	9.5	10.2	9.1
30	9.2	8.2	9.1	8.0	9.0	7.9
25	8.5	7.5	8.5	7.4	8.3	7.2
20	8.0	7.0	8.0	6.9	7.8	6.7
15	7.4	6.4	7.3	6.2	7.1	6.0
10	6.3	5.3	6.4	5.3	6.2	5.1
5	4.3	3.3	4.2	3.1	4.2	3.1

\*Includes contributions of: wind stress, barometric pressure, dynamic wave set-up and astronomical tide.



## REFERENCES

1. Dean, R. G., Chiu, T. Y. and Wang, S. Y., "Combined Total Storm Tide Frequency for Sarasota County, Florida," Beaches and Shores Resource Center, Florida State University, August 1988.
2. U. S. Department of Commerce, National Oceanic and Atmospheric Administration, "Storm Climatology for the Atlantic and Gulf Coasts of the United States," NOAA Technical Report NWS 38, April 1987.
3. U. S. Department of Commerce, National Oceanic and Atmospheric Administration, "Storm Best Track Files (HURDAT), 1851 – 2009," <http://www.nhc.noaa.gov>.

**APPENDIX A**

**SUMMARY OF HISTORICAL STORMS AFFECTING  
SARASOTA COUNTY**

#	Date	Name	$\theta_N$ (degrees)	$Y_F$ (n.mi.)	$V_F$ (knots)	$\Delta p$ (in.Hg)	R (n.mi.)	Type
1	9/9/1903		119	32	8.2	-0.74		E
2	10/9/1910		190	-53	10.2	-1.72	16	L
3	10/20/1921		229	51	10.6	-1.8	18	L
4	10/14/1924		263	-92	8.1	-1.12	19	L
5	11/27/1925		214	-38	24.0	-0.64		L
6	9/11/1926		127	-43	10.0	-1.86	17	E
7	9/19/1929		116	-132	6.9	-1.36		E
8	8/29/1935		148	25	11.8	-1.51	21	A
9	10/30/1935		72	-132	13.1	-1.18	10	E
10	10/3/1941		128	-47	18.0	-1.66	18	E
11	10/12/1944		189	-14	16.2	-1.00	27	L
12	6/20/1945		243	95	11.0	-0.97		L
13	10/5/1946		186	26	16.1	-1.00		L
14	9/4/1947		108	-72	6.5	-1.09	34	E
15	10/9/1947		225	-135	10.0	-0.74		L
16	9/18/1948		204	-128	6.6	-1.48	7	L
17	9/1/1950	EASY	204	59	4.4	-1.63	15	L
18	8/29/1960	DONNA	158	0	9.7	-2.04	20	A
19	10/8/1964	ISBELL	224	-110	18.0	-1.33	10	L
20	8/27/1965	BETSY	99	-136	13.5	-1.80	19	E
21	6/4/1966	ALMA	159	37	17.2	-1.15	23	A
22	10/13/1968	GLADYS	227	74	7.3	-1.07	21	L
23	8/16/1992	ANDREW	97	-105	17.0	-1.83	16	E
24	10/12/1999	IRENE	212	-138	11.8	-0.80		L
25	9/14/2000	GORDON	202	108	9.7	-0.83	23	L
26	8/9/2004	CHARLEY	200	-36	21.2	-1.95	7	L
27	8/25/2004	FRANCES	149	96	7.0	-0.95	40	E
28	8/23/2005	KATRINA	64	-124	6.9	-0.77	7	E
29	10/15/2005	WILMA	237	-92	22.2	-1.77	41	L
30	10/10/1900		243	150	17.9	-0.24		L
31	8/2/1901		101	-15	5.4	-0.24		E
32	6/12/1902		165	72	10.4	-0.38		A
33	10/12/1904		259	-119	5.4	-0.18		L
34	10/8/1906		12	-63	13.3	-0.14	35	E
35	9/18/1907		111	-83	11.4	-0.14		E
36	9/24/1909		238	-78	9.4	-0.14		L
37	8/8/1911		156	70	6.6	-0.24		A
38	10/26/1911		236	91	26.8	-0.18		L
39	10/3/1912		261	119	12.6	-0.14		L
40	9/25/1920		243	101	28.9	-0.46		L
41	10/15/1921		215	-40	18.4	-0.14		L
42	8/7/1928		149	22	10.5	-0.46		A
43	8/29/1930		227	25	7.3	-0.24		L
44	8/26/1932		122	-74	11.5	-0.38		E
45	7/25/1933		90	16	6.2	-0.31		E

#	Date	Name	$\theta_N$ (degrees)	$Y_F$ (n.mi.)	$V_F$ (knots)	$\Delta p$ (in.Hg)	R (n.mi.)	Type
46	5/27/1934		207	-104	15.7	-0.24		L
47	7/21/1934		71	114	15.1	-0.24		E
48	6/12/1936		276	-90	19.7	-0.24		L
49	7/27/1936		129	40	8.0	-0.54		A
50	7/29/1937		222	48	13.3	-0.24		L
51	8/7/1939		125	125	8.7	-0.54		E
52	8/2/1940		69	85	8.6	-0.18		E
53	10/15/1941		222	133	5.4	-0.31		L
54	9/3/1945		132	15	18.0	-0.18		A
55	9/20/1947		193	66	8.2	-0.38		L
56	10/18/1950	LOVE	207	115	17.9	-0.54		L
57	9/28/1951	HOW	262	-30	14.4	-0.46		L
58	2/2/1952		222	-130	29.5	-0.18		L
59	8/28/1953		270	-80	12.5	-0.83		L
60	10/7/1953	HAZEL	233	-31	20.0	-0.54		L
61	6/18/1959		240	28	32.0	-0.14		L
62	10/17/1959	JUDITH	260	-30	18.0	-0.42		L
63	7/28/1960	BRENDA	229	117	31.0	-0.14		L
64	6/2/1964		229	121	16.6	-0.14		L
65	6/1/1968	ABBY	213	-30	13.1	-0.59		L
66	10/1/1969	JENNY	197	-69	9.4	-0.39		L
67	6/24/1974		229	40	19.9	-0.39		L
68	8/18/1976	DOTTIE	222	-126	21.4	-0.21		L
69	8/7/1981	DENNIS	196	-142	3.1	-0.45		L
70	6/18/1982		225	80	22.6	-0.30		L
71	7/21/1985	BOB	270	-53	11.0	-0.24		L
72	11/17/1988	KEITH	246	14	14.6	-0.53		L
73	10/9/1990	MARCO	167	12	8.2	-0.71		A
74	11/8/1994	GORDON	207	-54	7.9	-0.48		L
75	7/31/1995	ERIN	107	97	13.9	-0.68		E
76	10/22/1998	MITCH	238	-63	19.0	-0.68		L
77	9/19/1999	HARVEY	275	-85	11.6	-0.50	33	L
78	9/11/2001	GABRIELLE	218	2	11.5	-0.89	14	L
79	9/3/2003	HENRI	245	51	16.7	-0.24	28	L
80	9/2/2004	IVAN	84	-93	9.8	-0.12		E
81	5/31/2007	BARRY	200	42	28.7	-0.39	17	L
82	8/15/2008	FAY	202	-93	9.7	-0.56	33	L

Landfalling Storms = 53 ; Alongshore Storms = 9 ; Exiting Storms = 20

<sup>1</sup> Values are estimated prior to landfall.

**APPENDIX B**

COMPUTED 15 AND 25 YEAR HYDROGRAPHS FOR  
SARASOTA COUNTY

