



Department of Environmental Protection

Jeb Bush
Governor

Twin Towers Office Building
2600 Blair Stone Road
Tallahassee, Florida 32399-2400

David B. Struhs
Secretary

December 9, 2002

Mr. Mark Simmons
American BioMatrix Incorporated
1121 South Military Trail #220
Deerfield Beach, Florida 33442

Re: **BioSolve**

Dear Mr. Simmons:

The Bureau of Petroleum Storage Systems hereby reaffirms its acceptance of BioSolve as an innovative product for enhancing the biodegradation of petroleum contaminants in groundwater or soil, in situ or ex situ. This reaffirmation supersedes the original October 13, 1998 acceptance letter and all subsequent revisions to it prior to this date. There are no regulatory or technical changes in this revision, only a change of address. It may be noteworthy that there have not been any changes regarding groundwater monitoring required for the following BioSolve intermediate degradation products of environmental concern: nonylphenol (NP), nonylphenol monoethoxylate (NPE₁), and nonylphenol diethoxylate (NPE₂).

BioSolve is a proprietary product manufactured by the Westford Chemical Corporation of Westford, Massachusetts. It is a biodegradable, nonionic and slight anionic surfactant having several uses. It is listed by the United States Environmental Protection Agency as a surface washing agent in the National Oil and Hazardous Substances Pollution Contingency Plan, and by Underwriter's Laboratories as a wetting agent for fire fighting. The United States Department of Agriculture has accepted it as a surface cleaning agent for the processing of meat and poultry. Enclosure 1 is a voucher for the confidential disclosure of its proprietary ingredients to the Florida Department of Environmental Protection.

For vadose remediation where the underlying groundwater will not be affected by the leaching of BioSolve, there are no special concerns beyond those which would normally need to be addressed in preparing a Remedial Action Plan and conducting a cleanup in accordance with the petroleum cleanup requirements of Chapter 62-770, Florida Administrative Code (F.A.C.). For ex situ groundwater treatment, where an aboveground treatment system produces effluent meeting the petroleum cleanup criteria of Chapter 62-770, F.A.C., and the drinking water standards of Chapter 62-550, F.A.C., for disposal via recharge gallery or NPDES permit, there are no special concerns. But for in situ groundwater remediation, via direct injection of BioSolve into an aquifer, there are underground injection control (UIC) regulations that must be observed. Since in situ aquifer remediation via injection is likely to be the most common application of this product, the bulk of the regulatory requirements discussed herein will be directed to that topic.

Mr. Mark Simmons
December 9, 2002
Page 2

The bureau recognizes BioSolve as a viable product for the bioremediation of petroleum contaminated sites in Florida. There are no objections to its use provided: (a) the considerations of this letter are taken into account; (b) a Remedial Action Plan is approved by the Department; and (c) the terms of a May 23, 2001 variance granted by the Department to American Environmental of Broward County Incorporated are observed. The terms of the variance - which temporarily allows a zone of discharge where the secondary drinking water standard for pH, and the minimum groundwater criteria for nonylphenol, nonylphenol monoethoxylate, and nonylphenol diethoxylate may be exceeded - are summarized in enclosure 2. The May 23, 2001 variance for these four parameters supersedes the original January 8, 1999 variance that applied only to pH.

While the Department of Environmental Protection does not provide endorsement of specific or brand name remediation products or processes, it does recognize the need to determine their acceptability from an environmental standpoint with respect to applicable rules and regulations, and the interests of public health, safety, and welfare. Vendors must then market the products and processes on their own merits regarding performance, cost, and safety in comparison to competing alternatives in the marketplace. In no way, however, shall this regulatory acceptance letter be construed as Department certification of product or process performance.

Preparers of Remedial Action Plans are advised to include a copy of this letter in the appendix of plans they submit, and call attention to it in the text of their document. In this way, technical reviewers throughout the state will be informed that you have contacted the Department of Environmental Protection to inquire about the environmental acceptability of BioSolve. To aid those reviewers, the Bureau of Petroleum Storage Systems provides supplemental information as enclosure 3.

The Department reserves the right to revoke its acceptance of a product or process if its proprietary ingredients, its performance, or any other significant aspect has been falsely represented. Additionally, Department acceptance of any product or process does not imply it has been deemed applicable for all cleanup situations, or that it is preferred over other treatment or cleanup techniques in any particular case. A site specific evaluation of applicability and cost-effectiveness must be considered for any product or process, whether conventional or innovative, and adequate site specific design details must be provided in a Remedial Action Plan.

You may contact me at 850/245-8911 if there are any questions.

Sincerely,

Rick Ruscito, P.E.
Bureau of Petroleum Storage Systems

c: Ronald LaRoche, President

Mr. Mark Simmons
December 9, 2002
Page 3

Westford Chemical Corporation
P.O. Box 798
Westford, Massachusetts 01886

T. Conrardy - FDEP/Tallahassee

George Heuler - FDEP/Tallahassee

History:

inn_021.doc
ppl #022
10/13/1998

inn_021c.doc
ppl #123
5/31/2001

inn_021d.doc
12/9/02

Department of Environmental Protection

Jeb Bush
GovernorTwin Towers Office Building
2600 Blair Stone Road
Tallahassee, Florida 32399-2400David B. Struhs
Secretary

December 9, 2002

Mr. Mark Simmons
American BioMatrix Incorporated
1121 South Military Trail #220
Deerfield Beach, Florida 33442

Re: BioSolve Proprietary Ingredients Voucher

Dear Mr. Simmons:

The Bureau of Petroleum Storage Systems hereby acknowledges receipt of a confidential disclosure dated September 28, 1998, submitted by the Westford Chemical Corporation on October 1, 1998, regarding the proprietary ingredients and their proportions in the bioremediation product for petroleum known as BioSolve.

BioSolve is a nonionic and a slight anionic biodegradable surfactant that may be applied as a 3 to 6 percent aqueous solution (usually by volume) for enhancing the bioremediation of petroleum hydrocarbon contaminants in soil or groundwater, in situ or ex situ.

Having reviewed the confidential disclosure, we hereby vouch for its composition, and hereby indicate that pH, nonylphenol (NP), nonylphenol monoethoxylate (NPE₁), and nonylphenol diethoxylate (NPE₂) are the environmental parameters of concern associated with the product when it is injected into aquifers for remediation purposes. These parameters are regulated by the drinking water standards and the minimum groundwater standards of Chapters 62-550 and 62-520 of the Florida Administrative Code (F.A.C.) respectively, and are referenced by the underground injection control requirements of Chapter 62-528, F.A.C. The pH range for the BioSolve concentrations proposed for injection is marginal, ranging from 8.6 to 9.14, in comparison to the acceptable 6.5 to 8.5 range set forth in the secondary drinking water standards of Chapter 62-520, F.A.C. The BioSolve intermediate degradation products NP, NPE₁, and NPE₂, that could be present for a period of time before ultimately degrading to carbon dioxide and water, are regulated by the minimum groundwater criteria of Chapter 62-520, F.A.C.

For underground injection control purposes, remediation plans proposing BioSolve must disclose the volume and composition of the fluid to be injected into an aquifer. Since the composition is proprietary, it will suffice to indicate the overall concentration of the BioSolve solution (which will range from 3 to 6 percent by volume) and provide a footnote indicating that a one-time confidential disclosure regarding the proprietary composition has been submitted to the Department and accepted. Reference should be made to the original September 28, 1998 disclosure, and a copy of this voucher should be included as an appendix in the plan. Remediation plans proposing the use of BioSolve should also observe the groundwater monitoring requirements for pH, NP, NPE₁, and NPE₂ that were imposed by the variance from Rule 62-522.300(3),

Mr. Mark Simmons
December 9, 2002
Page Two

BioSolve
December 9, 2002

F.A.C., that was granted May 23, 2001. The May 23, 2001 variance for these four parameters supersedes the original January 8, 1999 variance that applied only to pH.

Remediation plan reviewers for petroleum contaminated site applications involving BioSolve may contact me at (850) 245-8911.

Sincerely,

Rick Ruscito, P.E.
Bureau of Petroleum Storage Systems

ENCLOSURE 2

BIOSOLVE: ENVIRONMENTAL AND REGULATORY CONSIDERATIONS

For BioSolve applications, the major environmental and regulatory considerations are listed below.

- a. Groundwater cleanup standards: The onus shall be on users of BioSolve to ensure that all applicable groundwater contaminant standards will be met at the time of project completion, for petroleum and any residuals associated with the ingredients of BioSolve, and any byproducts produced as a result of chemical or biochemical reactions involving those ingredients. The following chapters of the Florida Administrative Code are cited: Chapter 62-550, F.A.C., for primary and secondary water quality standards; Chapter 62-520, F.A.C. for groundwater classes and standards; Chapter 62-522, F.A.C., for groundwater permitting and monitoring requirements; Chapter 62-528, F.A.C., for underground injection control, particularly Part V, for Class V, Group 4 aquifer remediation projects; and Chapter 62-770, F.A.C., for petroleum cleanup criteria.

A noteworthy aspect of the minimum criteria set forth in Chapter 62-520, F.A.C., is that it requires groundwater to be free from substances which are harmful to plants, animals, and organisms, and free from substances that are carcinogenic, mutagenic, teratogenic or toxic to human beings. In effect, these "free from" requirements form a catchall. They close what would otherwise be a loophole in the regulations by preventing injection of a potentially harmful product in the event that any of its ingredients is not regulated as a specific primary or secondary drinking water contaminant.

- b. Injection well permit: The issuance of a site specific Remedial Action Plan Approval Order by either the Bureau of Petroleum Storage Systems or the Bureau of Waste Cleanup, for remediation via injection of BioSolve into an aquifer, constitutes the granting of a Class V injection well permit.
- c. Groundwater injection standards: For in situ aquifer remediation, the composition of an injected fluid must meet the drinking water standards set forth in Chapter 62-550, F.A.C., pursuant to underground injection control Rule 62-528.600(2)(d), F.A.C.
- d. Variance summary: A May 23, 2001 variance, which supersedes an earlier January 8, 1999 variance, granted to American Environmental of Broward County Incorporated is for a temporary exemption from Rule 62-522.300(3), F.A.C., in order to create a 35 foot zone of discharge in the aquifer around each injection point. Within this zone of discharge, for a period of time not to exceed one (1) year, a temporary departure from the secondary drinking water standard set forth for pH in Chapter 62-550, F.A.C., and the minimum groundwater criteria for NP, NPE₁, and NPE₂, pursuant to Chapter 62-520, F.A.C., will be tolerated when BioSolve is injected for remediation purposes. By the end of the 1-year period, the groundwater must meet the required values for these parameters, or the natural-occurring background value for each of them at a given remediation site, whichever is less stringent. The current secondary drinking water standard for pH is 6.5 - 8.5, and the

minimum groundwater criteria determined for each of NP, NPE₁, and NPE₂, pursuant to Chapter 62-520, F.A.C., is 8.4 parts per billion, which is equivalent to 8.4 micrograms per liter (ug/L).

The variance granted by the Department is a general variance, which may be applied to each site-specific BioSolve Remedial Action Plan submitted hereafter. American Environmental of Broward County Incorporated does not have to petition for a new variance each time BioSolve is proposed for the remediation of a site, provided there is no deviation from the terms of the variance.

- e. Utilization of wells: If a remediation site happens to have an abundance of monitoring wells, then the Department has no objection to the use of some wells for the application of BioSolve. However, no "designated" monitoring well, dedicated to the tracking of remediation progress (by sampling), shall be used to apply BioSolve. This will avoid premature conclusions that the entire site meets cleanup goals. By making sure that designated tracking wells are not also used for treatment, there will be more assurance that the treatment process has permeated the entire site and that it did not remain localized to the area immediately surrounding each injection well.
- f. Nutrients option: BioSolve does not contain nutrients for bioremediation. If nutrients are found to be lacking at a particular remediation site, then they may be artificially introduced. However, the injection of such nutrients into an aquifer must be in accordance with the underground injection control requirements of Chapter 62-528, F.A.C., which requires that substances injected into an aquifer meet the drinking water standards set forth Chapter 62-550, F.A.C., and the minimum groundwater criteria of Chapter 62-520, F.A.C.
- g. Bioaugmentation option: BioSolve does not contain microorganisms. If the injection of bacteria will accompany the use of BioSolve, then only microorganisms that are naturally occurring (not genetically engineered) and non-pathogenic (do not cause disease) shall be used.
- h. Groundwater monitoring:
 - 1. Active remediation petroleum monitoring: During the period of active remediation, groundwater shall be monitored in accordance with the requirements set forth in Section 62-770.700, F.A.C. Two noteworthy rules within that section are 62-770.700(3)(i), F.A.C., for frequency of sampling, and 62-770.700(5)(f), F.A.C., which requires a sampling schedule for bioremediation.
 - 2. Post remediation petroleum monitoring: At least one (1) year of quarterly post remediation groundwater monitoring shall be conducted at a minimum of two (2) wells, one located in the area of maximum petroleum contamination, the other downgradient of the area of maximum petroleum contamination, pursuant to Section 62-770.750, F.A.C.
 - 3. Underground injection control monitoring: Since pH of the injected BioSolve may not meet the secondary drinking water standard set forth in Chapter 62-550, F.A.C., and the intermediate degradation products NP, NPE₁, and NPE₂ may not

meet the minimum groundwater criteria, pursuant to Chapter 62-520, F.A.C., the Department, pursuant to Rules 62-528.615(1)(b)1 and (2), F.A.C., has determined that measurements of pH, NP, NPE₁, and NPE₂ in the aquifer shall be made for underground injection monitoring purposes. The terms of the May 23, 2001 variance require that the background levels of these parameters be measured outside the contamination plume prior to injection, and monitored downgradient after injection. Additionally, the Bureau of Petroleum Storage Systems recommends that these parameters also be monitored in the area of the contamination plume where the BioSolve was actually injected. The purpose of monitoring after injection is to demonstrate that pH, NP, NPE₁, and NPE₂ either meet their respective groundwater criteria or do not exceed their natural-occurring background levels, whichever is less stringent.

- i. Underground injection control inventory: Remedial Action Plans prescribing in situ aquifer injection-type remediation shall include information pursuant to Rule 62-528.630(2)(c)1 through 6, F.A.C., for the inventory purposes of underground injection control. Per Rule 62-528.630(2)(c), F.A.C., aquifer remediation projects involving injection wells may be authorized under the provisions of a Remedial Action Plan, provided the construction, operation, and monitoring requirements of Chapter 62-528, F.A.C., are met. A memorandum outlining the inventory information about injection type aquifer remediation plans to be transmitted by Department reviewers to the Underground Injection Control Section is provided as enclosure 4. Only reviewers within the Department, including its district offices, may approve in situ injection-type remediation plans in which the approval constitutes a Class V injection permit; local programs are not authorized to grant such approvals. See enclosure 3.
- j. Operation:
 1. Avoidance of migration: For in situ injection-type aquifer remediation projects, injection of BioSolve shall be performed in such a way, and at such a rate and volume, that no undesirable migration of either the product's ingredients or the petroleum contaminants in the aquifer results, pursuant to Rule 62-528.630(3), F.A.C.
 2. Underground injection control operating permit: Although an operating permit is not required for aquifer remediation wells pursuant to Rule 62-528.640(1)(b), and 62-528.640(1)(c), F.A.C., since no movement of the petroleum contamination plume is expected to accompany the BioSolve treatment process, the Department requests that the information items listed in Rule 62-528.640(1)(b), F.A.C., be considered and included in Remedial Action Plan proposals as a matter of good and thorough design practice. Briefly summarized, they are: quality of water in the aquifer; quality of the injected fluid; existing and potential uses of the affected aquifer; and well construction details. Additionally, each Remedial Action Plan should clearly indicate the total volume and concentration of BioSolve that will be injected.
 3. Operating parameter measurements: Rule 62-770.700(9)(h), F.A.C., sets forth frequency requirements for the measurement of bioremediation operating parameters such as dissolved oxygen

levels, rates of nutrient addition, temperature, etc. It also includes an option for reduction in the frequency or discontinuation of some measurements in situations when appropriate.

- k. Abandonment of wells: Upon issuance of a petroleum Site Rehabilitation Completion Order, or a declaration of "No Further Action", injection wells shall be abandoned pursuant to Section 62-528.645, F.A.C. The Underground Injection Control Section of the Department shall be notified so that the injection wells can be removed from the inventory tracking list.

ENCLOSURE 3

BIOSOLVE: SUPPLEMENTAL INFORMATION

The information below, compiled from several sources, may be helpful to reviewers of Remedial Action Plans prescribing bioremediation.

- a. Department of Environmental Protection reviewers of in situ injection-type aquifer remediation plans, regardless of whether in Tallahassee or district offices, must fill in the blanks on the enclosure 4 memorandum, whose subject is "Proposed Injection Well(s) for In Situ Aquifer Remediation at a Petroleum Remedial Action Site". The completed form must be submitted to the Underground Injection Control Section at 2600 Blair Stone Road, Tallahassee, Florida 32399-2400.

Only reviewers within the Department and its district offices may approve in situ injection type remediation plans in which the approval constitutes the issuance of a Class V injection permit; local programs are not authorized to grant such approvals. Reason: Although an arrangement between the Environmental Protection Agency and the Department delegates underground injection control authority to the Department, it does not allow the Department to delegate that authority any further. This includes delegation to the Department's contracted remediation review agencies such as those operated by the counties and other local governments.

- b. Pilot study: For bioremediation, per rule 62-770.700(2), F.A.C., a pilot study proposal shall be submitted for review, and a pilot test shall be performed prior to designing a treatment system. If conditions or the situation at a site do not warrant a pilot study, then a proposal explaining the rationale for the decision not to perform a pilot study shall be submitted for review. For state funded projects, reviewers are encouraged to use judgment in balancing cost and the need for technical information to be obtained from a pilot study.
- c. Dosage and application rate: It has been indicated that BioSolve will usually be applied as an aqueous solution whose concentration is 3 to 6 percent (usually by volume but possibly by weight since both measures are roughly equal for this product). For in situ treatment, BioSolve may be applied using injection wells or direct push methods. Petroleum remediation projects conducted in New Jersey (for groundwater) and California (for vadose) injected approximately 250 gallons per well at a rate of 2 to 5 gallons per minute. For the California project, during each injection, the application rate was approximately one (1) gallon of 2% BioSolve solution for every 7.5 cubic yards of contaminated media within the injection well's radius of influence.
- d. Oxygen: BioSolve is a chemical surfactant. It does not act as an oxygen source for bioremediation. Oxygen, either as pure O₂ or atmospheric air, must be provided separately by the user if aerobic biodegradation of the petroleum contaminants is to occur.
- e. Case history: For the California vadose remediation project, eight (8) injections of BioSolve were made during an 18 month period, with the observed effective radius of influence being approximately 20 feet. Unwanted migration of contaminants was

avoided by making the first injections at the perimeter of the contamination plume and then working inward to its center.

- f. Hydraulic control: In situations where liquid phase hydrocarbons are present as free floating product on the water table, and BioSolve is to be used to increase product mobility to speed recovery, consideration should be given to the need for hydraulic control in order to prevent the spread of contamination. The Bureau of Petroleum Storage Systems believes that the implementation of hydraulic control will not be an issue in most free product recovery cases since pumps, vacuum pumps, or skimmers are usually part of such a recovery effort anyway.
- g. Degradation products: Carbon dioxide and water are the ultimate products of aerobic and most anaerobic biodegradations of petroleum hydrocarbons. The intermediate products may include simple acids, alcohols, and fatty acids. Aerobic processes use oxygen as an electron acceptor to produce the carbon dioxide and water.

As for the environmental fate of BioSolve itself, the manufacturer indicates that carbon dioxide and water account for almost all of the ultimate decomposition products, citing literature about the type of surfactants it contains. The May 23, 2001 variance that was granted addresses the monitoring of the intermediate NP, NPE₁ and NPE₂ degradation products that may be present for a period of time prior to ultimate decomposition.

The Bureau of Petroleum Storage Systems notes that there is also a small amount of sodium (Na) and sulfur (S) in the molecular structure of a particular ingredient, which will not form carbon dioxide or water. For such a small amount of these chemical species in a 3% BioSolve injection fluid, it can be reasoned that their ultimate degradation products will not be present in sufficient concentration so as to violate a secondary drinking water standard of Chapter 62-550, F.A.C. For sodium, the standard is 160 milligrams per liter (mg/L), and for sulfate it is 250 mg/L. The bureau, in developing the rationale for this position, assumes that all of the sodium will be ionized, and that all of the sulfur will react to ultimately form sulfate.

- h. Parameters: The following parameters may be useful in determining the potential for bioremediation at a site, or whether bioremediation is already occurring. They were selected from a list that appears in the publication "In Situ Treatment Technology" by E. Nyer et al., Lewis Publishers, 1996. The parameters are: dissolved oxygen; redox potential; pH; temperature; specific conductance; volatile organic compounds; nitrate; nitrite; ammonia nitrogen; manganese (total and dissolved); iron (total, dissolved, and ferrous); sulfate; sulfide; and total organic carbon. Gaseous parameters include: carbon dioxide, oxygen, nitrogen, and methane. Other parameters that may be helpful are chemical oxygen demand, biochemical oxygen demand, and total organic carbon. Preparers of bioremediation plans and their reviewers should determine which parameters, if any, should be investigated on a site specific basis.
- i. Operating parameters: Some key bioremediation parameters are listed below, along with their typical ranges and optimum values. They are provided as guidance only and should not be construed as

absolute, or used as the sole criteria for approval or disapproval of proposed Remedial Action Plans or remediation status reports.

Total nitrogen:	50-100 mg/L	
Total phosphorus:	50-100 mg/L	
Temperature:	10-40 deg. C	(30 deg. C, optimum)
Moisture content (for soil):	15-20%	
pH:	4.5-9.0	(7.0, optimum)
Dissolved oxygen:	2 ppm minimum	(> 3 ppm, optimum)
Carbon/nitrogen ratio:	20 to 1, maximum	(10 to 1, optimum)

2002

**Florida Department of
Environmental Protection**

Memorandum

TO: Richard Deuerling, Mail Station 3530
Division of Water Facilities
Underground Injection Control Section
Florida Department of Environmental Protection
2600 Blair Stone Road, Tallahassee, FL 32399-2400

FROM: _____ (Note 1.)

DATE: _____

SUBJ: **Proposed Injection Well(s) for In Situ Aquifer
Remediation at a Petroleum Remedial Action Site**

Pursuant to Rule 62-528.630(2)(c), F.A.C, inventory information is hereby provided regarding the proposed construction of temporary injection well(s) for the purpose of in situ aquifer remediation at a petroleum-contaminated site.

Site name: _____
Site address: _____
City/County: _____
Latitude/Longitude: _____
FDEP Facility Number: _____

Site owner's name: _____
Site owner's address: _____

Well contractor's name: _____ (Note 2.)
Well contractor's address: _____

Brief description of the in situ injection-type aquifer remediation project:

Summary of major design considerations and features of the project:

Areal extent of contamination (square feet): _____
Number of injection wells: _____
Composition of injected fluid (Note 3)
(ingredient, wt. %): _____

Injection volume per well (gallons): _____
Single or multiple injection events: _____
Injection volume total (all wells, all
events): _____

A site map showing the areal extent of the groundwater contamination plume, and the location and spacing of injection wells and associated monitoring wells is attached.

The following is a summary description of the affected aquifer:

Name of aquifer: _____

Depth to groundwater (feet): _____
Aquifer thickness (feet): _____

The injection well(s) features are summarized below, and/or a schematic of the injection well(s) is attached.

Direct-push or Conventional (*circle the appropriate well type*)
Diameter of well(s) (i.e., riser pipe & screen)(inches): _____
Total depth of well(s) (feet): _____
Screened interval: _____ to _____ feet below surface
Grouted interval: _____ to _____ feet below surface
Casing diameter, if applicable (inches): _____
Cased depth, if applic.: _____ to _____ feet below surface
Casing material, if applic.: _____

The in situ injection-type aquifer remediation plan for this petroleum contaminated site is intended to meet the groundwater petroleum cleanup criteria set forth in Chapter 62-770, F.A.C. Additionally, all other groundwater standards will be met at the time of project completion for any residuals associated with the ingredients of the injected remediation products, and any by-products or intermediates produced as a result of the chemical or biochemical transformation of those ingredients or the contaminating petroleum during their use. Applicable primary and secondary drinking water standards are set forth in Chapter 62-550, F.A.C., and additional groundwater quality criteria are set forth in Chapter 62-520, F.A.C.

The remediation plan estimates that site remediation will take _____ months. We will notify you if there are any modifications to the remediation strategy which will affect the injection well design or the chemical composition and volume of the injected remediation product(s).

The proposed remediation plan was approved on _____ by an enforceable approval order. A copy is attached. The remediation system installation is expected to commence within 60 days. Please call me at _____ if you require additional information.

Note 1. Local programs are not authorized to approve underground injections into aquifers. Reason: Per agreement with EPA, the FDEP cannot delegate this authority. Local programs, after reviewing a Remedial Action Plan or an injection proposal document, should follow the instructions in a March 16, 2000 memorandum to arrange for Department headquarters' execution of an approval order, and then complete this form. This form is primarily for use by state and local program technical reviewers, but petroleum remediation contractors may fill in all blanks except those labeled "FROM", "DATE", and "approval date", and "telephone number" blanks in the last paragraph. Those blanks should be completed only by a state or local program reviewer.

Note 2. If an injection well installation contractor has not yet been selected, then indicate the name and address of the project's general remediation contractor/consultant.

Note 3. Complete chemical analysis of injected fluid is required by Chapter 62-528, Florida Administrative Code. Proprietary formulations shall make confidential disclosure. Injected fluids must meet drinking water standards of Chapter 62-550, F.A.C., unless an exemption or variance has been granted.